



armfield


OSBORNE REYNOLDS' APPARATUS

F5

issue 14



Laminar flow



Transitional laminar-turbulent flow

A robust item of equipment designed to reproduce the classic experiments of Professor Osborne Reynolds

DEMONSTRATION CAPABILITIES

- *To compute Reynolds' No. (R_e)*
- *To observe and quantify transitional flow*
- *To observe the paraboloid velocity profile*

Basic Fluid Mechanics



DESCRIPTION

The Armfield Osborne Reynolds' Apparatus can be bench or floor mounted and is designed for the vertical flow of a liquid through a precision bore glass tube.

The use of a vertical direction for the flow compensates for the effect of any small deviations of the density of dye relative to that of the working fluid.

The operating fluid may be supplied from any small bore supply point by means of the flexible hose provided. Fluid enters a cylindrical constant head tank through a ring diffuser and then through a stilling bed to eliminate any gross variations of fluid velocity in the head tank.

This tank therefore provides uniform, low velocity head conditions upstream of the entry to the vertically mounted pipe test section. Fluid enters this section through a profiled bellmouth, designed to uniformly accelerate the fluid without any spurious inertial effects.

The cylindrical pipe test section is mounted inside a fabricated shroud that provides an uninterrupted white background for observations of the dye trace behaviour. Dye solution is admitted to the test section through a fine diameter stainless steel tube and the rate of flow of dye is controlled by a needle valve on the outlet of the dye reservoir. The dye injection system can be readily removed for cleaning and maintenance.

The flow rate of the working fluid through the test section is regulated by a globe valve located in the base of the apparatus. The rate may be measured either volumetrically

or by weighing (equipment for this purpose is not supplied). The apparatus is compatible with any means chosen to alter the kinematic viscosity of the fluid, either by using different fluids or by altering the temperature of a given fluid (the external circuit for this is not supplied).

The whole apparatus is mounted on a substantial fabricated steel support and a means is provided for levelling the apparatus to ensure the test section is vertical.

The stilling bed, all necessary connecting hoses, an initial supply of dye and an instruction manual are supplied with the apparatus.

ORDERING SPECIFICATION

- **Floor standing apparatus to produce classic Osborne Reynolds' experiments.**
- **Fluid enters a vertically mounted test section through a carefully profiled bellmouth from a constant head tank.**
- **An easily cleaned dye injection system is incorporated.**
- **Fluid flow is controlled by a needle point globe valve.**
- **Supply includes stilling bed, hoses and dye.**

SERVICES

Water supply: Up to 0.5 litres/sec maximum.

OVERALL DIMENSIONS

Height: 1.48m
Diameter: 0.61m

SHIPPING SPECIFICATION

Volume: 1.2m³
Gross weight: 130kg

Armfield Limited
Bridge House, West Street, Ringwood,
Hampshire BH24 1DY, England

Tel: +44 (0)1425 478781 Fax: +44 (0)1425 470916
E mail: sales@armfield.co.uk
URL: <http://www.armfield.co.uk>

USA Office:
Armfield Inc.

436 West Commodore Blvd (#2)
Jackson NJ 08527

Tel: (732) 928-3332 Fax: (732) 928-3542
E mail: info@armfieldinc.com